



產品規範書  
specification

## PRODUCT NAME

產品名稱

BOPP PACKAGING TAPE  
BOPP包裝膠帶

MAKER 製表	基材 Backing	BOPP	
姚佳奴	膠系 Adhesive	壓克力油膠 Acrylic Emulsion	
	顏色 Color	超透明 Super Clear	
<b>特性</b> <b>Feature</b>	項目 Item	標準規範 Standard Value	檢驗方式 Test Method
黏性強、抗壓力佳、耐候性佳。 High adhesion, high tensile strength and weather-resistance.	外觀 Appearance	不能打皺、色差、空隙 No wrinkle, interval and	目視
	厚度 (mm) Thickness	0.075±0.002	PSTC-133
<b>應用</b> <b>Application</b>	黏著力(kg/in) Peel adhesion	0.6↑	PSTC-101
適用一般包裝封箱固定用，且廣泛用於自動封箱機器。 Widely used for common sealing or light weight packaging, also widely used for automatic sealing machine.	保持力(min) Holding power	1440↑	PSTC-7
	抗拉強度 (kg/in) Tensile Strength	5.1↑	PSTC-131
	延伸率 (%) Elongation	100↑	PSTC-131

## 備註

### Remark

\* 客戶需依其實際操作需求與目的，進行產品測試與確認，或通知本公司，以提供進一步說明與服務。

Customers need to test and confirm products for the actual operational requirement and purpose or inform us to supply the further introduction and service.

\* 本表僅提供參考，不可作為驗收標準。

Above information is for reference only and should not be as inspection standard.

\* 以上數據資料皆為在室溫 $23\pm2^{\circ}\text{C}$ 及濕度 $50\pm5\%$ 所測試結果。

Above information are completed under room temperature  $23\pm2^{\circ}\text{C}$  and humidity  $50\pm5\%$ .